



INTERNATIONAL STANDARD ISO/IEC 15444-12:2008
TECHNICAL CORRIGENDUM 4

Published 2011-05-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — JPEG 2000 image coding system —
Part 12:
ISO base media file format

TECHNICAL CORRIGENDUM 4

Technologies de l'information — Système de codage d'images JPEG 2000 —

Partie 12: Format ISO de base pour les fichiers médias

RECTIFICATIF TECHNIQUE 4

Technical Corrigendum 4 to ISO/IEC 15444-12:2008 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

In 6.2.3, Box order, Table 1, Box types, structure, and cross-reference, remove the following line:

		tsel					8.10.3	track selection
--	--	------	--	--	--	--	--------	-----------------

In 6.2.3, Table 1, insert the following lines between 'subs' and 'mvex':

		udta					8.10.1	user-data
			tsel				8.10.3	track selection

In 8.3.3.1, replace:

This box provides a reference from the containing track to another track in the presentation. These references are typed. A 'hint' reference links from the containing hint track to the media data that it hints. A content description reference 'cdsc' links a descriptive or metadata track to the content which it describes.

with:

This box provides a reference from the containing track to another track in the presentation. These references are typed. A 'hint' reference links from the containing hint track to the media data that it hints. A content description reference 'cdsc' links a descriptive or metadata track to the content which it describes. The 'hind' dependency indicates that the referenced track(s) may contain media data required for decoding of the track containing the track reference. The referenced tracks shall be hint tracks. The 'hind' dependency can, for example, be used for indicating the dependencies between hint tracks documenting layered IP multicast over RTP.

In 8.7.3.1, add at the end:

NOTE A sample size of zero is not prohibited in general, but it must be valid and defined for the coding system, as defined by the sample entry, that the sample belongs to.

In 8.8.3.1, replace:

```

bit(4)    reserved=0;
unsigned int(2) is_leading;
unsigned int(2) sample_depends_on;
unsigned int(2) sample_is_depended_on;
unsigned int(2) sample_has_redundancy;
bit(3)    sample_padding_value;
bit(1)    sample_is_difference_sample;
          // i.e. when 1 signals a non-key or non-sync sample
unsigned int(16) sample_degradation_priority;

```

with:

```

bit(4)    reserved=0;
unsigned int(2) is_leading;
unsigned int(2) sample_depends_on;
unsigned int(2) sample_is_depended_on;
unsigned int(2) sample_has_redundancy;
bit(3)    sample_padding_value;
bit(1)    sample_is_non_sync_sample;
unsigned int(16) sample_degradation_priority;

```

and after:

The is_leading, sample_depends_on, sample_is_depended_on and sample_has_redundancy values are defined as documented in the Independent and Disposable Samples Box.