



International Standard

ISO/ASTM 52967

**First edition
2024-10**

Additive manufacturing for aerospace — General principles — Part classifications for additive manufactured parts used in aviation

*Fabrication additive pour l'aéronautique — Principes généraux —
Classification de pièces pour les pièces produites par fabrication
additive utilisées dans l'aviation*

STANDARDSISO.COM : Click to view the full PDF of ISO/ASTM 52967:2024



COPYRIGHT PROTECTED DOCUMENT

© ISO/ASTM International 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester. In the United States, such requests should be sent to ASTM International.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11

Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

ASTM International
100 Barr Harbor Drive, PO Box C700
West Conshohocken, PA 19428-2959, USA
Phone: +610 832 9634
Fax: +610 832 9635
Email: khooper@astm.org
Website: www.astm.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Referenced Documents	2
3 Terminology	3
4 Part Classification Designations	3
Annex A (Mandatory Information)	4
Bibliography	11

STANDARDSISO.COM : Click to view the full PDF of ISO/ASTM 52967:2024

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted (see www.iso.org/directives).

ASTM International is one of the world's largest voluntary standards development organizations with global participation from affected stakeholders. ASTM technical committees follow rigorous process due to balloting procedures.

ISO and ASTM International draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and ASTM International take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and ASTM International had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO and ASTM International shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by ASTM Committee F42, *Additive manufacturing technologies* (as ASTM F3752-22) and drafted in accordance with its editorial rules. It was assigned to Technical Committee ISO/TC 261, *Additive manufacturing*, and adopted under the "fast-track procedure".

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The use of additive manufacturing (AM) technology allows designs that may not be achieved with traditional manufacturing methods. It is important to understand the risk associated with the AM usage by understanding the consequence of failure (including the loss of intended function) of the usage. Such information can be beneficial in establishing consistent manufacturing, inspection, or qualification processes relative to a defined risk scale, which can serve as supporting data when seeking regulatory approval of an AM part. A part classification scheme based on a part's consequence of failure can provide a consistent risk metric. Without carefully defined part classes, the ability to accurately gauge the consequence of failure associated with additively manufactured aviation parts within and across programs, projects, and suppliers becomes exceedingly difficult, resulting in mitigations that are either not commensurate or inconsistent. The part classification scheme documented here does not affect a part's functional requirements, but rather is used to group additive manufacturing aviation parts into categories which can be used in downstream standards. For example, this classification scheme can be used in material and process specifications to determine the appropriate levels of process control, thermal post processing, qualification, and inspection to ensure AM parts meet their application requirements. This classification scheme does not specify how the classification is used in any downstream processes. The use of the classification shall be left to the cognizant engineering or production entities, or downstream documents which reference this standard.

STANDARDSISO.COM : Click to view the full PDF of ISO/ASTM 52967:2024

Additive manufacturing for aerospace — General principles — Part classifications for additive manufactured parts used in aviation

1 Scope

- 1.1** This practice is intended to be used to assign part classifications across the aviation industries that use AM to produce parts.
- 1.2** This practice is applicable to all AM technologies defined in ISO/ASTM 52900 used in aviation.
- 1.3** This practice is intended to be used to establish a metric for AM parts in downstream documents.
- 1.4** This practice is not intended to establish criteria for any downstream processes, but rather to establish a metric that these processes can use.
- 1.5** The part classification metric could be utilized by the engineering, procurement, non-destructive inspection, testing, qualification, or certification processes used for AM aviation parts.
- 1.6** The classification scheme in this practice establishes a consistent methodology to define and communicate the consequence of failure associated with AM aviation parts.
- 1.7** This practice is not intended to supersede the requirements and definitions of the applicable regulations or policies, including but not limited to the ones listed in Annex A1.

Tables A.1.1-A.1.3 align the existing regulations and guidance with the four part classes established herein. However, this alignment should not be construed as an alignment of the existing regulations to each other.

- 1.9** The material or process, or both, in general does not affect the consequence of failure of a part, therefore the classification scheme defined in this document may be used outside AM.
- 1.10** The user of this standard should not assume regulators' endorsement of this standard as accepted mean of compliance.
- 1.11** *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*
- 1.12** *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2 Referenced Documents

2.1 ISO/ASTM Standards:¹⁾

52900 Additive Manufacturing – General principles – Fundamentals and vocabulary

2.2 United States Department of Defense Standards:²⁾

MIL-STD-882 Standard Practice System Safety

MIL-STD-1530 Aircraft Structural Integrity Program (ASIP)

MIL-STD-1798 Mechanical Equipment and Subsystems Integrity Program

2.3 NASA Standard:³⁾

NASA-STD-6030 Additive Manufacturing Requirements for Spaceflight Systems

2.4 AWS Standard:⁴⁾

AWS D20 Specification for Fabrication of Metal Components using Additive Manufacturing

2.5 AMS Standard:⁵⁾

AMS2175 Castings, Classification and Inspection of

2.6 FAA Regulations and Guidance Materials:

AC43-18 Fabrication of Aircraft Parts by Maintenance Personnel⁶⁾⁷⁾

AC25.571 Damage Tolerance and Fatigue Evaluation of Structure⁷⁾

AC25.1309 System Design and Analysis⁷⁾

AC33.70-1 Guidance Material for Aircraft Engine Life-Limited Parts Requirements⁷⁾

AC33-8 Guidance for Parts Manufacturer Approval of Turbine Engine and Auxiliary Power Unit Parts under Test and Computation⁷⁾

14CFR27.602 Critical Part⁷⁾

14CFR33.75 Safety Analysis⁸⁾

1) This specification is under the jurisdiction of ASTM Committee F42 on Additive Manufacturing Technologies and is the direct responsibility of Subcommittee F42.07 on Applications. Current edition approved July 1, 2022. Published August 2022. DOI: 10.1520/F3572-22.

2) Available from DLA Document Services, Building 4/D, 700 Robbins Ave., Philadelphia, PA 19111-5094, <https://quicksearch.dla.mil>.

3) Available Online: <https://standards.nasa.gov/standard/nasa/nasa-std-6030>.

4) Available from American Welding Society (AWS), 8669 NW 36 St., #130, Miami, FL 33166-6672, <http://www.aws.org>.

5) Available from SAE International (SAE), 400 Commonwealth Dr., Warrendale, PA 15096, <http://www.sae.org>.

6) Available from Federal Aviation Administration (FAA), 800 Independence Ave., SW, Washington, DC 20591, https://www.faa.gov/regulations_policies/advisory_circulars/.

7) Available from Federal Aviation Administration (FAA), 800 Independence Ave., SW, Washington, DC 20591, https://www.faa.gov/regulations_policies/faa_regulations

3 Terminology

3.1 Definitions of Terms:

3.1.1 Terminology in ISO/ASTM 52900 shall apply.

4 Part Classification Designations

4.1 Classifications:

4.1.1 All aviation parts produced using AM shall be classified in accordance with the four part classifications defined in [Table 1](#) and following the information found in Annex A1.

TABLE 1 — Part Classifications

Classification	Consequence of Failure	Non-exhaustive Examples
A	High	Part whose failure can directly affect continued safe flight and landing
		Part whose failure can result in serious or fatal injury to passengers or cabin crews
		Part whose failure requires exceptional piloting skill of flight crew to compensate
B	Medium	Part whose failure can indirectly affect continued safe flight and landing
		Part whose failure can result in minor injury to flight crew, passengers, or cabin crews
		Part whose failure can result in significant increase in workload of flight crew
C	Low	Part whose failure has no effect on continued safe flight and landing
		Part whose failure has no effect on flight crew, passengers, or cabin crew
		Part whose failure can result in slight reduction in operational/functional capabilities
D	Negligible or No Effect	Part whose failure can result in slight increase in workload of flight crew
		Part whose failure would pose no risk of damage to other equipment or injury to the ground personnel
		Parts not affecting operational/functional capabilities

4.2 Applicability:

4.2.1 The cognizant engineering or production entity shall determine the part classification considering the consequence of the failure of the part and the functional or systems requirements. The applicant for a design or production approval must seek individual guidance from their respective regulatory body concerning the use of this specification as part of a design or production approval.

4.3 Alignment with Regulations and Policies:

4.3.1 In order to evaluate if the part classification scheme is practical, the scheme was compared with the regulations and the guidance materials which are currently used in the aviation industry. Reference documents from both military ([Table A.1.1](#)) and civilian ([Table A.1.2](#)) domains covering both structural and non-structural aspects were reviewed. Other documents specific to spaceflight and broader non-aviation applications were also reviewed ([Table A.1.3](#)) as reference. The four-classification scheme works well with existing aviation regulatory documents. When establishing the specific methods of compliance, the user should refer to the original regulations (such as the ones listed in Annex A1).

Annex A

(Mandatory Information)

A.1 SUPPORTING DOCUMENTS

A.1.1 This annex is included to support the AM part classification designation in [Section 4](#). When establishing the specific methods of compliance, the user should refer to the original regulations.

TABLE A.1.1 — Alignment with Military Aviation Documents

F42 Classification	ARMY Policy 070-062	MIL-STD-1530 (ASIP)	NAVAIR Instruction 4790.41	JAMA (Joint AM Acceptability)	MIL-STD-1798	MI-STD-882
Class A	Category 6 Flight Parts/Components that Pose a Safety Impact to Include Critical Safety Items (CSIs)	Fracture Critical Traceable Part A fracture-critical traceable part is a safety-of-flight structural component that is either single load path or judged to require serialization and traceability. Fracture Critical Part A fracture-critical part is a safety-offflight structural component that is not single load path nor judged to require serialization and traceability.	Class IV Part consequence of failure: High - Critical Safety Items (CSIs)	Category 3 Items that pose a severe risk of damage to other equipment or personnel (for example, CSI)	Safety Critical Component	Category 1 (Catastrophic)
Class B	Category 5 Flight Parts/Components that Pose an Operational Impact but no Safety Impact	Durability Critical A non-safety-of-flight structural component that is judged to require additional controls beyond those for normal-control parts.	Class III Part consequence of failure: Medium - Critical Application Items (CAIs) - Not fatigue critical - Acceptable mission performance impact	Category 2 Items that pose a risk of damage to other equipment or personnel (for example, CAI)	Mission Critical Component	Category 2 (Critical)
Class C	Category 3 Flight Parts/Components with no Safety, Operation or Readiness Impact	Normal Controls Part A normal-controls part is a non-safety-of-flight structural component where standard aerospace practices are sufficient in the design, manufacturing, and maintenance of the part to ensure structural integrity.	Class II Part consequence of failure: Low - No safety consequence - Acceptable mission performance impact - Not fatigue critical - Not a CAI/CSI - Requires a flight clearance - Airworthiness impact	Category 1 Items that pose little risk of damage to other equipment or personnel (for example, not CSI or CAI)	Durability Critical Component Durability Non-Critical Component	Category 3 (Marginal) & Category 4 (Negligible)

TABLE A.1.1 (continued)

F42 Classification	ARMY Policy 070-062	MIL-STD-1530 (ASIP)	NAVAIR Instruction 4790.41	JAMA (Joint AM Acceptability)	MIL-STD-1798	MI-STD-882
Class D	Category 2 Aviation Ground Support Equipment Category 1 Fixtures, Jigs, Shop Aids and Tooling	N/A	Class I Part consequence of failure: Negligible - Non structural - No airworthiness impact - No risk of damage to other equipment or aircraft - No risk of injury to personnel	Category 0 Items that pose no risk of damage to other equipment or personnel (for example, not CSI or CAI)	Other/Expendable Component	N/A

STANDARDSISO.COM : Click to view the full PDF of ISO/ASTM 52967:2024

TABLE A.1.2 — Alignment with Civilian Aviation Documents

F42 Classification	AC43-18 Fabrication of Aircraft Parts Tolerance and Fatigue Evaluation by Maintenance Personnel	AC25.571 Damage Tolerance and Fa-	AC25.1309 System Design and Analysis	14 CFR§27.602/29.602 Critical Part	AC33.70-1 Guidance Material for Aircraft Engine Life-Limited Parts Requirements	14 CFR§33.75 Safety Analysis	AC33-8 Parts Manufacturer Approval of Turbine Engine and Auxiliary Power Unit Parts under Test and Computation
Class A	Category 1 A fabricated part, the failure of which could prevent continued safe flight and landing; resulting consequences could reduce safety margins, degrade performance, or cause loss of capability to conduct certain flight operations.	Principal Structural Element (AC25.571-1D) An element that contributes significantly to the carrying of flight, ground, or pressurization loads and whose integrity is essential in maintaining the overall structural integrity of the airplane	FHA = Hazardous or Critical Parts Catastrophic Large reduction in functional capabilities or safety margins on airplane. Serious or fatal injury to passengers or cabin crew. Excessive workload of flight crew. whose integrity is essential in maintaining the overall structural integrity of the airplane	Engine life-limited parts are rotor and major static structural parts whose primary failure is likely to result in a hazardous engine effect. Typically, engine life-limited parts include, but are not limited to disks, spacers, hubs, shafts, high-pressure casings, and non redundant mount components. For the purposes of this section, a hazardous engine effect is any of the conditions listed in §33.75 of this part.	SA = Hazardous Engine Effects: (i) Non-containment of high-energy debris; (ii) Concentration of toxic products in the engine bleed air intended for the cabin sufficient to incapacitate crew or passengers; (iii) Significant thrust in the opposite direction to that commanded by the pilot;	(iv) Uncontrolled fire; (v) Failure of the engine mount system leading to inadvertent engine separation; (vi) Release of the propeller by the engine, if applicable; and (vii) Complete inability to shut the engine down	Category 1. A product, i.e. engine, or part(s) thereof, whose failure could prevent continued safe flight and landing; resulting consequences could reduce safety margins, degrade performance, or cause loss of capability to conduct certain flight operations at Category 1 part, for the purpose of this AC, meets the definition of a critical part defined in Order 8110.42.

STANDARDS ISO.CN

2024

TABLE A.1.2 (continued)

		AC33-8 Parts Manufacturer Approval of Turbine Engine and Auxiliary Power Unit Parts under Test and Computation	
		AC33-70-1 Guidance Material for Aircraft Analysis	
		14 CFR§33.75 Safety Analysis	
		CFR§27.602/29.602 Critical Part	Parts Requirements
AC43-18 Fabrication of Aircraft Parts by Maintenance Personnel	AC25.571 Damage Tolerance and Fatigue Evaluation of Structure	AC25.1309 System Design and Analysis	14 CFR§27.602/29.602 Critical Part
F42 Classification	AC25.571 Damage Tolerance and Fatigue Evaluation of Structure	AC25.1309 System Design and Analysis	14 CFR§33.75 Safety Analysis
Class B	Category 2 A fabricated part, the failure of which would not prevent continued safe flight and landing, but would reduce the capability of the aircraft or the ability of the crew to cope with adverse operating conditions or subsequent failures.	FHA = Major Significant reduction in functional capabilities or safety margins on airplane. Physical distress, possibly including injuries to the occupants. A significant increase in workload of flight crew.	N/A
			N/A
			SA = Major Engine Effects: An effect whose severity falls between those effects identified as minor engine effects and hazardous engine effects.