NFPA® 1122

Code for Model Rocketry

2008 Edition



NFPA, 1 Batterymarch Park, Quincy, MA 02169-7471 An International Codes and Standards Organization

IMPORTANT NOTICES AND DISCLAIMERS CONCERNING NFPA DOCUMENTS

NOTICE AND DISCLAIMER OF LIABILITY CONCERNING THE USE OF NFPA DOCUMENTS

NFPA codes, standards, recommended practices, and guides, of which the document contained herein is one, are developed through a consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on fire and other safety issues. While the NFPA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy of any information or the soundness of any judgments contained in its codes and standards.

The NFPA disclaims liability for any personal injury, property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document. The NFPA also makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

In issuing and making this document available, the NFPA is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the NFPA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The NFPA has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does the NFPA list, certify, test or inspect products, designs, or installations for compliance with this document. Any certification or other statement of compliance with the requirements of this document shall not be attributable to the NFPA and is solely the responsibility of the certifier or maker of the statement.

ADDITIONAL NOTICES AND DISCLAIMERS

Updating of NFPA Documents

Users of NFPA codes, standards, recommended practices, and guides should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of Tentative Interim Amendments. An official NFPA document at any point in time consists of the current edition of the document together with any Tentative Interim Amendments and any Errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of Tentative Interim Amendments or corrected through the issuance of Errata, consult appropriate NFPA publications such as the National Fire Codes® Subscription Service, visit the NFPA website at www.nfpa.org, or contact the NFPA at the address listed below.

Interpretations of NFPA Documents

A statement, written or oral, that is not processed in accordance with Section 6 of the Regulations Governing Committee Projects shall not be considered the official position of NFPA or any of its Committees and shall not be considered to be, nor be relied upon as, a Formal Interpretation.

Patents

The NFPA does not take any position with respect to the validity of any patent rights asserted in connection with any items which are mentioned in or are the subject of NFPA codes, standards, recommended practices, and guides, and the NFPA disclaims liability for the infringement of any patent resulting from the use of or reliance on these documents. Users of these documents are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

NFPA adheres to applicable policies of the American National Standards Institute with respect to patents. For further information contact the NFPA at the address listed below.

Law and Regulations

Users of these documents should consult applicable federal, state, and local laws and regulations. NFPA does not, by the publication of its codes, standards, recommended practices, and guides, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the NFPA. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of safe practices and methods. By making this document available for use and adoption by public authorities and private users, the NFPA does not waive any rights in copyright to this document.

Use of NFPA documents for regulatory purposes should be accomplished through adoption by reference. The term "adoption by reference" means the citing of title, edition, and publishing information only. Any deletions, additions, and changes desired by the adopting authority should be noted separately in the adopting instrument. In order to assist NFPA in following the uses made of its documents, adopting authorities are requested to notify the NFPA (Attention: Secretary, Standards Council) in writing of such use. For technical assistance and questions concerning adoption of NFPA documents, contact NFPA at the address below.

For Further Information

All questions or other communications relating to NFPA codes, standards, recommended practices, and guides and all requests for information on NFPA procedures governing its codes and standards development process, including information on the procedures for requesting Formal Interpretations, for proposing Tentative Interim Amendments, and for proposing revisions to NFPA documents during regular revision cycles, should be sent to NFPA headquarters, addressed to the attention of the Secretary, Standards Council, NFPA, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101.

For more information about NFPA, visit the NFPA website at www.nfpa.org.

Copyright © 2007 National Fire Protection Association. All Rights Reserved.

NFPA 1122

Code for

Model Rocketry

2008 Edition

This edition of NFPA 1122, *Code for Model Rocketry*, was prepared by the Technical Committee on Pyrotechnics. It was issued by the Standards Council on June 4, 2007, with an effective date of June 24, 2007, and supersedes all previous editions.

This edition of NFPA 1122 was approved as an American National Standard on June 24, 2007.

Origin and Development of NFPA 1122

NFPA 1122 was created originally as a tentative code by the Technical Committee on Pyrotechnics as NFPA 41L, *Code for Model Rocketry*. It was adopted tentatively in 1967 and adopted officially by the Association in May 1968. In November 1976, a major revision of NFPA 41L, including its redesignation as NFPA 1122L, *Code for Unmanned Rockets*, was adopted. The 1976 edition was revised by the Technical Committee on Pyrotechnics in 1980 to eliminate the "L" designation and to delete the requirements for cold propellant model rocket motors, which no longer are allowed because of their use of chlorofluorocarbons (Freon 12TM). Other technical changes were made at that time. Those revisions were adopted at the 1981 NFPA Fall Meeting, and the new document became the 1982 edition. Amendments to the 1982 edition were processed at the 1986 NFPA Fall Meeting, resulting in the 1987 edition. Because of the rapid progress in consumer rocket technology and the emergence of the commercial space transportation industry, the 1987 edition was amended, and its title was changed back to NFPA 1122, *Code for Model Rocketry*, for the 1994 edition.

For the 1997 edition, the terminology and provisions relating to reloadable solid-propellant model rockets and reloadable solid-propellant model rocket motors were incorporated into the document for consistency with changes made to federal regulations that affected the model rocketry industry. These changes in federal regulations occurred after the previous edition of this code had been adopted. These changes were reflected throughout the document.

In addition, the citations for federal regulations were updated throughout the document to reflect changes made to those regulations since the previous edition of the code had been prepared.

Other changes were editorial in nature to bring the document into conformance with NFPA style.

The 2002 edition included a new edition of the National Association of Model Rocketry *Model Rocket Safety Code.* Other changes included deleting material covered by NFPA 1125 that was no longer needed in NFPA 1122. The code also was revised to comply with the *Manual of Style for NFPA Technical Committee Documents*.

The 2008 edition incorporates minor revisions to the standard; several definitions were amended to comply with the NFPA Glossary of Terms.

1122-2 MODEL ROCKETRY

Technical Committee on Pyrotechnics

James K. Lathrop, Chair Koffel Associates, Inc., CT [SE]

Kenneth L. Kosanke, Secretary PyroLabs, Incorporated, CO [SE]

Richard Bowes, Natural Resources Canada, Canada [RT] W. G. Bulifant, III, Dominion Fireworks, Inc., VA [U] Jose R. Colon, Connecticut Department of Public Safety,

Rep. International Fire Marshals Association John A. Conkling, Chestertown, MD [SE]

Randall W. A. Davidson, Risk International & Associates, Inc., CO [SE]

Vernon Estes, Canon City, CO [SE]

Gary A. Fadorsen, Pyrotech International Inc., OH [IM] **Phil Grucci**, Fireworks by Grucci, Inc., NY [M]

Garry Hanson, Precocious Pyrotechnics, Inc., MN [M] Rep. National Fireworks Association

Julie L. Heckman, American Pyrotechnics Association, MD [M]

Rep. American Pyrotechnics Association

John Hendrick, Natural Resources Canada, Canada [E] Lansden E. Hill, Jr., E. E. Hill & Son, Inc./Pyro Shows,

Bruce E. Kelly, Tripoli Rocketry Association, Inc., UT [U] Rep. Tripoli Rocketry Association, Inc.

John Kitchens, Los Angeles City Fire Department, CA [E]

Gerald R. Laib, U.S. Department of the Navy, MD [SE]

Peter M. Lamb, Town of Newport Fire-EMS, NH [E] Joshua Lazarus, State of New Jersey, NJ [E]

J. Patrick Miller, Hardin-Simmons University, TX [U]

Rep. National Association of Rocketry

David J. Pier, MP Associates, Inc., CA [M] Mary Roberts, Estes Industries, CO [M]

Gary C. Rosenfield, Industrial Solid Propulsion (ISP),

UT [M]

David S. Shatzer, U.S. Department of Justice, DC [E] James R. Souza, Pyro Spectaculars, Inc., CA [U]

John R. Steinberg, Pyrotechnics Guild International, Inc.,

Rep. Pyrotechnics Guild International, Inc.

Bill Stine, Quest Aerospace, Inc., AZ [M]

Lawrence Weinman, Luna Tech/Schneier-Weinman Consultants, TX [M]

Dan Westcott, Gadsden Fire Department, AL [E] Rep. NFPA Fire Service Section

Alternates

Arthur H. Barber, III, Springfield, VA [SE]

(Alt. to V. Estes)

Scot Bartel, Black Sky Research, CA [U]

(Alt. to B. E. Kelly)

Gary E. Brown, Pyro Spectaculars, Inc., CA [U] (Alt. to J. R. Souza)

Mark B. Bundick, National Association of Rocketry,

(Alt. to J. P. Miller)

Steve A. Coman, RES Specialty Pyrotechnics Inc., MN [U]

(Alt. to J. R. Steinberg)

Ettore Contestabile, Natural Resources Canada, Canada [RT]

(Alt. to R. Bowes)

H. Stephen Frantz, Western Enterprises, Inc., OK [U] (Alt. to L. E Hill, Jr.)

Felix J. Grucci, Jr., Fireworks by Grucci, Inc., NY [M] (Alt. to P. Grucci)

Alfred J. Hogan, Reedy Creek Improvement District, FL [E]

(Alt. to P. M. Lamb)

Bonnie J. Kosanke, Journal of Pyrotechnics, Inc., CO [SE]

(Alt. to K. L. Kosanke)

Larry Mars, MP Associates, Inc., CA [M]

(Alt. to D. J. Pier)

Brennan S. Phillips, U.S. Department of Justice, WA [E] (Alt. to D. S. Shatzer)

Gregg S. Smith, American Pyrotechnics Association, PA [M]

(Alt. to J. L Heckman)

John F. Thomas, III, City of Lancaster Bureau of Fire, PA[E]

(Voting Alt. to LBF Rep.)

Tad A. Trout, American Promotional Events, Inc., CA [U] (Alt. to W. G. Bulifant, III)

Gerald D. Ward, Bethany Fire Protection District, IL [E] (Alt. to D. Westcott)

Charles P. Weeth, Weeth & Associates, LLC, WI [SE] (Alt. to G. R. Laib)

William A. Weimer, B. J. Alan Company, OH [M] (Alt. to L. Weinman)

Nonvoting

Matthew I. Chibbaro, U.S. Department of Labor, DC [E] Joseph A. Domanico, U.S. Department of the Army,

MD [RT]

Guy R. Colonna, NFPA Staff Liaison

Mark W. Hagemann, U.S. Department of Labor, DC [E] (Alt. to M. I. Chibbaro)

Gary Zeller, Zeller International, NY [SE]



This list represents the membership at the time the Committee was balloted on the final text of this edition. Since that time, changes in the membership may have occurred. A key to classifications is found at the back of the document.

NOTE: Membership on a committee shall not in and of itself constitute an endorsement of the Association or any document developed by the committee on which the member serves.

Committee Scope: This Committee shall have primary responsibility for documents on the manufacture, transportation, and storage of consumer and display fireworks, pyrotechnic special effects, and model and high power rocket motors. This Committee shall have primary responsibility for the use of display fireworks and for model and high power rocketry, and the construction, launching, and other operations that involve model and high power rocket motors. The Committee shall have primary responsibility for documents on the wholesale and retail sale and storage of consumer fireworks.

The Committee does not have responsibility for documents on the use of consumer fireworks by the general public; on the use of pyrotechnic special effects before a proximate audience; on the manufacture, transportation, storage for use of military, automotive, agricultural, and industrial pyrotechnics.

1122–4 MODEL ROCKETRY

Contents

Chapter	1 Administration	1122-	5	4.9	Model Rocket Launch Site Size	1122-
1.1	Scope	1122-	5		Model Rocket Launchers	
1.2	Purpose	1122-	5	4.11	Model Rocket Launcher Eye Safety	1122- 8
1.3	Enforcement			4.12	Model Rocket Launch Safety	1122- 8
				4.13	Model Rocket Ignition System	1122- 8
Chapter	2 Referenced Publications				Spectator Distances	
2.1	General	1122–	5		Spectator Notification	
2.2	NFPA Publications	1122-	5		Model Rocket Misfires	
2.3	Other Publications	1122-	6	4.17	Model Rocket Launch Conditions	1122- 8
2.4	References for Extracts in Mandatory			4.18	Model Rocket Retrieval Safety	1122- 8
	Sections	1122-	6		Model Rocket Motor Requirements	
Chapter	3 Definitions			4.20	Residential Storage of Model Rocket Motors and Motor Components	1122- 8
3.2	NFPA Official Definitions			Chapter	5 Prohibited Activities	1122- 8
3.3	General Definitions			_	Prohibited Activities	
Chapter	4 Requirements for Model Rocket			Annex A	Explanatory Material	1122- 9
	Construction, Operation, and			Annex B	Madal Dacket Sufety Cada of the	
	Motor Storage	1122–	7	Ailliex D	Model Rocket Safety Code of the National Association of Rocketry	1199
4.1	Model Rocket Operations				National Association of Rocketty	1144-
4.2	Model Rocket Materials	1122-	7	Annex C Glossary		1122 –10
4.3	Model Rocket Recovery	1122-	7			
4.4	Model Rocket Weight Limits	1122-	7			
4.5	Model Rocket Power Limits	1122-	7			1122–10
4.6	Model Rocket Payloads	1122-	7	Annex E Informational References		1199_1
4.7	Model Rocket Flight Paths	1122-	7	Annex E	miorimatorial references	1144 ⁻ 1.
4.8	Model Rocket Launch Site	1199_	7	Index		1199_19



NFPA 1122

Code for

Model Rocketry

2008 Edition

IMPORTANT NOTE: This NFPA document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading "Important Notices and Disclaimers Concerning NFPA Documents." They can also be obtained on request from NFPA or viewed at www.nfpa.org/disclaimers.

NOTICE: An asterisk (*) following the number or letter designating a paragraph indicates that explanatory material on the paragraph can be found in Annex A.

Changes other than editorial are indicated by a vertical rule beside the paragraph, table, or figure in which the change occurred. These rules are included as an aid to the user in identifying changes from the previous edition. Where one or more complete paragraphs have been deleted, the deletion is indicated by a bullet (•) between the paragraphs that remain.

A reference in brackets [] following a section or paragraph indicates material that has been extracted from another NFPA document. As an aid to the user, the complete title and edition of the source documents for extracts in mandatory sections of the document are given in Chapter 2 and those for extracts in informational sections are given in Annex E. Editorial changes to extracted material consist of revising references to an appropriate division in this document or the inclusion of the document number with the division number when the reference is to the original document. Requests for interpretations or revisions of extracted text shall be sent to the technical committee responsible for the source document.

Information on referenced publications can be found in Chapter 2 and Annex E.

Chapter 1 Administration

1.1 Scope.

- 1.1.1 This code shall apply to the design, construction, limitation of rocket propellant mass and power, and reliability of model rocket motors and model rocket motor reloading kits and their components, produced commercially for sale to or for use by the public for purposes of education, recreation, and sporting competition.
- **1.1.2** This code also shall apply to the design and construction of model rockets propelled by model rocket motors specified in 1.1.1.
- **1.1.3** This code also shall apply to the conduct of launch operations of model rockets specified in 1.1.2.
- 1.1.4 This code shall not apply to the design, construction, production, manufacture, fabrication, maintenance, launch, flight, test, operation, use, or other activity that is connected with a rocket or rocket motor where carried out or engaged in by any of the following:
- (1) National, state, or local government

- (2) Individual, firm, partnership, joint venture, corporation, or other business entity engaged as a licensed business in the research, development, production, testing, maintenance, or supply of rockets, rocket motors, rocket propellant chemicals, or rocket components or parts
- (3) Colleges or universities
- 1.1.5 This code shall not apply to the design, construction, fabrication, maintenance, production, manufacture, launch, flight, test, operation, or use of rocket-propelled model aircraft that sustain their mass against the force of gravity by aerodynamic lifting surfaces that support the aircraft during the entire duration of its flight in the air, but shall apply to the model rocket motors and their components that provide the propulsion for such model aircraft.
- **1.1.6** This code shall not apply to model or toy rockets propelled by pressurized-liquid rocket motors containing less than 250 mL (8.45 fl oz) of water.
- **1.1.7** This code shall not apply to fireworks rockets or pyrotechnic rockets as defined in NFPA 1123, *Code for Fireworks Display*.
- 1.1.8 This code shall not apply to NFPA 1124, Code for the Manufacture, Transportation, Storage, and Retail Sales of Fireworks and Pyrotechnic Articles.
- **1.1.9** This code shall not apply to NFPA 1126, Standard for the Use of Pyrotechnics Before a Proximate Audience.
- **1.1.10** This code shall not apply to high power rocketry as defined in NFPA 1127, *Code for High Power Rocketry*.

1.2 Purpose.

- **1.2.1** The purpose of this code shall be to ensure the availability of commercial model rocket motors and components that meet standards of safety and reliability to ensure that the creative and experimental use of model rocket devices by the public is reasonably safe.
- **1.2.2** The purpose of this code also shall be to discourage the making and launching of homemade rockets and other rocket-like vehicles propelled by, or intended to be propelled by, homemade rocket-propulsion devices.
- 1.2.3 The purpose of this code also shall be to discourage experiments with explosive or highly energetic rocket propellants, construction of homemade rocket-propulsion motors, and attempted launchings or operations of these homemade rocket devices, thereby minimizing deaths and injuries.
- **1.3 Enforcement.** This code shall be administered and enforced by the authority having jurisdiction (AHJ) designated by the governing authority. (See Annex D for sample wording for enabling legislation.)

Chapter 2 Referenced Publications

- **2.1 General.** The documents or portions thereof listed in this chapter are referenced within this code and shall be considered part of the requirements of this document.
- **2.2 NFPA Publications.** National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02169-7471.

NFPA 1123, Code for Fireworks Display, 2006 edition.

NFPA 1124, Code for the Manufacture, Transportation, Storage, and Retail Sales of Fireworks and Pyrotechnic Articles, 2006 edition.



1122–6 MODEL ROCKETRY

NFPA 1125, Code for the Manufacture of Model Rocket and High Power Rocket Motors, 2007 edition.

NFPA 1126, Standard for the Use of Pyrotechnics Before a Proximate Audience, 2006 edition.

NFPA 1127, Code for High Power Rocketry, 2008 edition.

2.3 Other Publications.

2.3.1 U.S. Government Publications. U.S. Government Printing Office, Washington, DC 20402.

Title 14, Code of Federal Regulations, Parts 101.1–101.25, "Federal Aviation Administration Regulations."

Title 16, Code of Federal Regulations, Part 1500.85(8) and (9), "Consumer Product Safety Commission Regulations."

2.3.2 Other Publications.

Merriam-Webster's Collegiate Dictionary, 11th edition, Merriam-Webster, Inc., Springfield, MA, 2003.

2.4 References for Extracts in Mandatory Sections.

NFPA 1125, Code for the Manufacture of Model Rocket and High Power Rocket Motors, 2007 edition.

NFPA 1127, Code for High Power Rocketry, 2008 edition.

Chapter 3 Definitions

3.1 General. The definitions contained in this chapter shall apply to the terms used in this code. Where terms are not defined in this chapter or within another chapter, they shall be defined using their ordinarily accepted meanings within the context in which they are used. *Merriam-Webster's Collegiate Dictionary*, 11th edition, shall be the source for the ordinarily accepted meaning.

3.2 NFPA Official Definitions.

- **3.2.1* Approved.** Acceptable to the authority having jurisdiction.
- **3.2.2* Authority Having Jurisdiction (AHJ).** An organization, office, or individual responsible for enforcing the requirements of a code or standard, or for approving equipment, materials, an installation, or a procedure.
- **3.2.3* Code.** A standard that is an extensive compilation of provisions covering broad subject matter or that is suitable for adoption into law independently of other codes and standards.
- **3.2.4 Labeled.** Equipment or materials to which has been attached a label, symbol, or other identifying mark of an organization that is acceptable to the authority having jurisdiction and concerned with product evaluation, that maintains periodic inspection of production of labeled equipment or materials, and by whose labeling the manufacturer indicates compliance with appropriate standards or performance in a specified manner.
- **3.2.5* Listed.** Equipment, materials, or services included in a list published by an organization that is acceptable to the authority having jurisdiction and concerned with evaluation of products or services, that maintains periodic inspection of production of listed equipment or materials or periodic evaluation of services, and whose listing states that either the equipment, material, or service meets appropriate designated standards or has been tested and found suitable for a specified purpose.
- 3.2.6 Shall. Indicates a mandatory requirement.

3.2.7 Should. Indicates a recommendation or that which is advised but not required.

3.3 General Definitions.

3.3.1 Commercial Manufacturer. Any individual, firm, partnership, joint venture, corporation, or other business entity engaged in research, development, production, preparation, testing, maintenance, or supply of rockets, rocket motors, rocket propellant chemicals, rocket propellant, delay or ejection modules, or rocket components or parts.

3.3.2 Engine.

- **3.3.2.1** *Model Rocket Engine.* See 3.3.5.2.2, Model Rocket Motor.
- **3.3.2.2** Rocket Engine. See 3.3.5.2, Rocket Motor.
- **3.3.3 Installed Total Impulse.** The combined total impulse of all rocket motors installed in a rocket and intended to be ignited during the launch and flight of the rocket.
- **3.3.4 Module.** A pyrotechnic component of a reloadable model rocket motor in which the chemical composition is loaded into a finished assembly by the manufacturer.

3.3.5 Motor.

- **3.3.5.1** *Certified Motor.* A commercially manufactured rocket motor that has been certified by a recognized testing organization acceptable to the authority having jurisdiction to meet the certification requirements set forth in NFPA 1125, *Code for the Manufacture of Model Rocket and High Power Rocket Motors.*
- **3.3.5.2*** *Rocket Motor.* A device containing propellant that provides the force or thrust to cause a rocket to move.
- **3.3.5.2.1** *High Power Rocket Motor.* A rocket motor that has more than 160 N-sec (36 lb-sec) but no more than 40,960 N-sec (9208 lb-sec) of total impulse, or that produces an average thrust of greater than 80 N (18 lbf), or that contains greater than 62.5 g (2.2 oz) of propellant. [1125, 2007]
- **3.3.5.2.2*** *Model Rocket Motor.* A rocket motor that has a total impulse of no greater than 160 N-sec (36 lb-sec), an average thrust of no greater than 80 N (18 lbf), and a propellant weight of no greater than 62.5 g (2.2 oz), and that otherwise meets the other requirements set forth in NFPA 1125, Code for the Manufacture of Model Rocket and High Power Rocket Motors.
- **3.3.5.2.3** *Reloadable Rocket Motor.* A rocket motor that has been designed and manufactured so that the user can load, reload, and reuse the pressure-containing body or casing using the parts and components of a motor-reloading kit. [1125, 2007]
- **3.3.5.2.4** *Solid-Propellant Rocket Motor.* A rocket motor that contains a fuel and an oxidizer in solid form and whose force or thrust is produced by the combustion of the fuel and oxidizer.
- **3.3.6* Motor Reloading Kit.** A product manufactured by a commercial manufacturer that contains the components and parts used to reload and reuse a reloadable rocket motor casing.
- **3.3.7 Rocket.** A device that ascends into the air without the use of aerodynamic lifting forces acting against gravity and that is propelled by one or more rocket motor(s).



- **3.3.7.1** *High Power Rocket.* A rocket vehicle that (1) is propelled by one or more high power rocket motors; or (2) is propelled by a combination of model rocket motors having an installed total impulse of more than 320 N-sec (71.9 lb-sec); or (3) is propelled by a combination of model rocket motors having more than a total of 125 g (4.4 oz) of propellant weight; or (4) weighs more than 1500 g (53 oz) with motor(s) installed. [1127, 2008]
- **3.3.7.2*** *Model Rocket.* A rocket that (1) weighs no more than 1500 g (53 oz) with motors installed; and (2) is propelled by one or more model rocket motors having an installed total impulse of no more than 320 N-sec (71.9 lb-sec); and (3) contains no more than a total of 125 g (4.4 oz) of propellant weight.
- **3.3.8 Rocket Propellant.** The material(s) utilized in a rocket motor that produces thrust by the discharge of a working fluid generated by combustion, decomposition, change of state, or other operation of such material contained within the rocket motor.
- **3.3.9 Structural Parts.** The load-bearing parts of a model rocket, specifically, the nose cone, body tube, and fins.

Chapter 4 Requirements for Model Rocket Construction, Operation, and Motor Storage

4.1* Model Rocket Operations. A model rocket shall comply with the requirements of construction and operation as set forth in 14 CFR 101.1–101.25, "Federal Aviation Administration Regulations."

4.2 Model Rocket Materials.

- **4.2.1** A model rocket's structural parts, including the body, nose cone, and fins, shall be made of paper, wood, or plastic and shall contain no metal parts.
- **4.2.2** A model rocket motor casing that is metallic, reloadable, and meets the specifications in this code shall be permitted.
- **4.2.3** A model rocket motor shall be assembled with all pyrotechnic ingredients preloaded into a cylindrical paper or similarly constructed nonmetallic tube that does not fragment into sharp, hard pieces.

4.3* Model Rocket Recovery.

- **4.3.1** A model rocket shall have a means for returning it to the ground (for example, a parachute) so that it can be flown again.
- **4.3.2** All recovery wadding used in a model rocket shall be flame-resistant.

4.4* Model Rocket Weight Limits.

- $\bf 4.4.1~A~model~rocket~shall~weigh~no~more~than~453~g~(16~oz)$ at lift-off, including rocket propellant.
- **4.4.2** A model rocket shall use no more than 113 g (4 oz) of rocket propellant, unless one of the following is met:
- (1)*A model rocket that weighs in excess of 453 g (16 oz), but not more than 1500 g (53 oz), including rocket propellant, shall be permitted if the Federal Aviation Administration notice requirements are met.

- (2) A model rocket that uses more than 113 g (4 oz), but less than or equal to 125 g (4.4 oz) of rocket propellant, shall be permitted if the Federal Aviation Administration notice requirements are met.
- **4.5 Model Rocket Power Limits.** A model rocket's installed motor(s) shall produce a total impulse of no more than 320 N-sec (71.9 lb-sec).
- **4.6 Model Rocket Payloads.** A model rocket shall not carry a payload that is designed to be flammable, explosive, or harmful to persons or property.
- **4.7 Model Rocket Flight Paths.** A model rocket shall not be launched on a flight path aimed at a target.
- **4.8 Model Rocket Launch Site.** A model rocket shall be launched outdoors in a cleared area, free of tall trees, power lines, buildings, and dry brush and grass.
- **4.9** Model Rocket Launch Site Size. The launch site shall be at least as large as specified in Table 4.9.

Table 4.9 Minimum Launch Site Dimensions

Installed Total		Minimum Site Dimension	
Impulse (N-sec)	Equivalent Motor Type	m	ft
0-1.25	1/4 A and 1/2 A	15	50
1.26 - 2.50	A	30	100
2.51 - 5.00	В	61	200
5.01 - 10.00	\mathbf{C}	122	400
10.01-20.00	D	152	500
20.01-40.00	E	305	1000
40.01-80.00	F	305	1000
80.01-160.00	2F (or 1G)	305	1000
160.01-320.00	4F (or 2G)	457	1500

- **4.9.1** For a circular area, the minimum launch site dimension shall be the diameter; and for a rectangular area, it shall be the shortest side.
- **4.9.2** A model rocket with an installed total rocket propellant weight exceeding 113 g (4 oz), but less than or equal to 125 g (4.4 oz) shall comply with the additional operating notice requirements as set forth in 14 CFR 101.1–101.25, "Federal Aviation Administration Regulations."
- **4.9.3** Type G motors with an installed total impulse of more than 80 N-sec (18 lb-sec), but not more than 160 N-sec (36 lb-sec), shall be permitted to be used by individuals 18 years of age and older.
- **4.9.4** As an alternative to the minimum launch site dimensions of Table 4.9, the size of the launch site shall meet one of the following criteria:
- (1) It shall be not less than one-half the maximum altitude as stated by the manufacturer for the model rocket and motor(s) combination being flown.
- (2) It shall be of a size approved by the AHJ based on flight demonstration or data required to substantiate the anticipated altitude.
- **4.10 Model Rocket Launchers.** A model rocket shall be launched from a stable launch device that provides rigid guidance until it has reached a speed adequate to ensure a safe flight path.

1122–8 MODEL ROCKETRY

4.11 Model Rocket Launcher Eye Safety.

- **4.11.1** To prevent accidental eye injury, the launcher shall be placed so the end of the rod is above eye level, or the end shall be capped when approaching it.
- **4.11.2** The launch rod shall be capped or disassembled when not in use and shall not be stored in an upright position.

4.12 Model Rocket Launch Safety.

- **4.12.1** The launcher shall have a blast deflector device to prevent the motor exhaust from hitting the ground directly.
- **4.12.2** The area around a launch device shall be cleared of brown grass, dry weeds, or other easy-to-burn materials.

4.13 Model Rocket Ignition System.

- **4.13.1** The system used to launch a model rocket shall be remotely controlled and electrically operated.
- **4.13.2** The system shall have a launching switch that returns to the "off" position when released.
- **4.13.3** The system shall be equipped with a removable safety interlock in series with the launch switch.

4.14 Spectator Distances.

- **4.14.1** All persons shall remain at least $4.6~\mathrm{m}$ (15 ft) from the model rocket during ignition of a model rocket motor with an installed total impulse of $30~\mathrm{N}\text{-sec}$ (6.7 lb-sec) or less.
- **4.14.2** All persons shall remain at least 9 m (30 ft) from the model rocket during ignition of a model rocket motor with an installed total impulse of more than 30 N-sec (6.7 lb-sec).

4.15 Spectator Notification.

- **4.15.1** All people in the launch area shall be made aware of the pending model rocket launch.
- **4.15.2** An audible 5-second countdown to launch shall take place.
- **4.16 Model Rocket Misfires.** If a model rocket misfires, no person shall approach the launcher until 1 minute has elapsed and the safety interlock has been removed or the battery has been disconnected from the ignition system.

4.17 Model Rocket Launch Conditions.

- **4.17.1** A model rocket shall not be launched in a wind of more than 32 km/h (20 mph).
- 4.17.2 A model rocket shall not be launched into a cloud.
- **4.17.3** A model rocket shall not be launched near an aircraft in flight.
- **4.17.4** A model rocket shall not be launched at an angle greater than 30 degrees from vertical.
- **4.18* Model Rocket Retrieval Safety.** No attempt shall be made to retrieve a model rocket from a power line or other life-threatening area.

4.19 Model Rocket Motor Requirements.

- **4.19.1** Only commercially manufactured, certified model rocket motors or motor reloading kits or components as specified in NFPA 1125, *Code for the Manufacture of Model Rocket and High Power Rocket Motors*, shall be used.
- **4.19.2** No person shall dismantle, reload, or alter a single-use model rocket motor.

4.19.3 No person shall alter the components of a reloadable model rocket motor or use the contents of a reloadable rocket motor reloading kit for a purpose other than those specified by the manufacturer's instructions for the reloadable rocket motor or reloading kit.

4.20 Residential Storage of Model Rocket Motors and Motor Components.

- **4.20.1** Not more than 23 kg (50 lb) net weight of solid-propellant model rocket motors, motor reloading kits, or motor components shall be stored at a residence.
- **4.20.2** Not more than 11 kg (25 lb) net weight of solid-propellant model rocket motors, motor reloading kits, or motor components stored at a residence shall be permitted to be stored in the living quarters.
- **4.20.3** Provisions for the storage of more than 23 kg (50 lb) net weight of solid-propellant model rocket motors, motor reloading kits, or motor components at a residence shall be subject to the approval of the AHJ.

Chapter 5 Prohibited Activities

- **5.1 Prohibited Activities.** The following activities shall be prohibited by this code:
- (1) Using model rocket motors, motor reloading kits, or components for the primary purpose of producing a spectacular display of color, light, sound, or any combination thereof
- (2) Using a model rocket or model rocket motor, motor reloading kit, or component as a weapon
- (3) Using a model rocket, model rocket motor, motor reloading kit, or component contrary to the instructions for its use
- (4) Tampering with any model rocket motor or motor reloading kit or component in any manner or to any degree that is contrary to the purpose for which the model rocket motor, motor reloading kit, or component is designed and intended to be used
- (5) Making, operating, launching, flying, testing, activating, discharging, or other experimentation with model rocket motors, motor reloading kits, or motor components that have not been certified in accordance with NFPA 1125, Code for the Manufacture of Model Rocket and High Power Rocket Motors
- (6) Selling, offering for sale, exposing for sale, purchasing, making, or using fuse, wick, or other ignition devices intended to be activated by a handheld flame for the purpose of starting or igniting a model rocket motor
- (7) Exhibiting statements in writing, in advertising, or on packaging that certification in accordance with NFPA 1125, Code for the Manufacture of Model Rocket and High Power Rocket Motors, has been obtained, when such certification has not been obtained, has been withdrawn, or has been denied
- (8) Reloading any expendable solid-propellant model rocket motor with any material after that motor has been operated
- (9) Reloading any reloadable model rocket motor with any material or by any means not specifically provided or recommended by the manufacturer
- (10) Purchasing or using by persons 17 years of age or younger of Type G model rocket motors that do not meet the specifications of 16 CFR 1500.85(8) and (9), "Consumer Product Safety Commission Regulations."



(11) Purchasing or using by persons 17 years of age or younger of reloadable model rocket motors or motor reloading kits that do not meet the specifications of 16 CFR 1500.85(8) and (9), "Consumer Product Safety Commission Regulations."

Annex A Explanatory Material

Annex A is not a part of the requirements of this NFPA document but is included for informational purposes only. This annex contains explanatory material, numbered to correspond with the applicable text paragraphs.

- **A.3.2.1 Approved.** The National Fire Protection Association does not approve, inspect, or certify any installations, procedures, equipment, or materials; nor does it approve or evaluate testing laboratories. In determining the acceptability of installations, procedures, equipment, or materials, the authority having jurisdiction may base acceptance on compliance with NFPA or other appropriate standards. In the absence of such standards, said authority may require evidence of proper installation, procedure, or use. The authority having jurisdiction may also refer to the listings or labeling practices of an organization that is concerned with product evaluations and is thus in a position to determine compliance with appropriate standards for the current production of listed items.
- **A.3.2.2 Authority Having Jurisdiction (AHJ).** The phrase "authority having jurisdiction," or its acronym AHI, is used in NFPA documents in a broad manner, since jurisdictions and approval agencies vary, as do their responsibilities. Where public safety is primary, the authority having jurisdiction may be a federal, state, local, or other regional department or individual such as a fire chief; fire marshal; chief of a fire prevention bureau, labor department, or health department; building official; electrical inspector; or others having statutory authority. For insurance purposes, an insurance inspection department, rating bureau, or other insurance company representative may be the authority having jurisdiction. In many circumstances, the property owner or his or her designated agent assumes the role of the authority having jurisdiction; at government installations, the commanding officer or departmental official may be the authority having jurisdiction.
- **A.3.2.3 Code.** The decision to designate a standard as a "code" is based on such factors as the size and scope of the document, its intended use and form of adoption, and whether it contains substantial enforcement and administrative provisions.
- **A.3.2.5 Listed.** The means for identifying listed equipment may vary for each organization concerned with product evaluation; some organizations do not recognize equipment as listed unless it is also labeled. The authority having jurisdiction should utilize the system employed by the listing organization to identify a listed product.
- **A.3.3.5.2 Rocket Motor.** The force or thrust is created by the discharge of gas generated by combustion, decomposition, change of state, or other operation of materials contained, carried, or stored solely within the rocket motor or rocket and not dependent on the outside environment for reaction mass.
- **A.3.3.5.2.2 Model Rocket Motor.** Where the term *model rocket motor* is used in this code, it includes both assembled, reloadable model rocket motors and manufactured, expendable model rocket motors.
- **A.3.3.6 Motor Reloading Kit.** The components and parts normally include a rocket propellant module(s), a new model

rocket motor nozzle, new insulation components, prepackaged delay and ejection modules, an electrical igniter, and the parts necessary to seal the casing during operation.

- **A.3.3.7.2 Model Rocket.** A model rocket has structural parts made of paper, wood, and breakable plastic; it has a means for its return to the ground so it can be flown again; and its primary use is for purposes of education, recreation, and sporting competition.
- **A.4.1** The following is an excerpt from 14 CFR 101.1, "Federal Aviation Administration Regulations":
- (a) This part prescribes rules governing the operation in the United States of the following:
 - (1) ...
 - (2) ...
 - (3) Any unmanned rocket except:
 - (i) Aerial fireworks displays; and,
 - (ii) Model rockets:
 - (a) Using not more than four ounces of propellant;
 - (b) Using a slow-burning propellant;
 - (c) Made of paper, wood, or breakable plastic, containing no substantial metal parts, and weighing not more than 16 ounces, including the propellant; and
 - (d) Operated in a manner that does not create a hazard to persons, property, or other aircraft.
- **A.4.3** Models should be launched only during daylight hours.
- **A.4.4** A model rocket should weigh no more than the motor manufacturer's recommended maximum lift-off weight for the motors used or should use motors recommended by the kit manufacturer.
- **A.4.4.2(1)** See 14 CFR 101.1–101.25, "Federal Aviation Administration Regulations."
- **A.4.18** It is recommended that, if a model rocket becomes entangled in a power line, the utility company or other appropriate authority be notified.

Annex B Model Rocket Safety Code of the National Association of Rocketry

This annex is not a part of the requirements of this NFPA document unless specifically adopted by the jurisdiction.

B.1 The *Model Rocket Safety Code* provides guidance applicable to activities involving model rockets for education, recreation, and sporting competition. The National Association of Rocketry also publishes an annotated version of the *Model Rocket Safety Code*.

Model Rocket Safety Code

National Association of Rocketry

Adopted February 2001

- **1. Materials.** I will use only lightweight, non-metal parts for the nose, body, and fins of my rocket.
- **2. Motors.** I will use only certified, commercially-made model rocket motors, and will not tamper with these motors or use them for any purposes except those recommended by the manufacturer.

- **3. Ignition System**. I will launch my rockets with an electrical launch system and electrical motor igniters. My launch system will have a safety interlock in series with the launch switch, and will use a launch switch that returns to the "off" position when released.
- **4. Misfires.** If my rocket does not launch when I press the button of my electrical launch system, I will remove the launcher's safety interlock or disconnect its battery, and will wait 60 seconds after the last launch attempt before allowing anyone to approach the rocket.
- **5. Launch Safety.** I will use a countdown before launch, and will ensure that everyone is paying attention and is a safe distance of at least 4.6 m (15 ft) away when I launch rockets with D motors or smaller, and 9.1 m (30 ft) when I launch larger rockets. If I am uncertain about the safety or stability of an untested rocket, I will check the stability before flight and will fly it only after warning spectators and clearing them away to a safe distance.
- **6. Launcher**. I will launch my rocket from a launch rod, tower, or rail that is pointed to within 30 degrees of the vertical to ensure that the rocket flies nearly straight up, and I will use a blast deflector to prevent the motor's exhaust from hitting the ground. To prevent accidental eye injury, I will place launchers so that the end of the launch rod is above eye level or will cap the end of the rod when it is not in use.
- **7. Size.** My model rocket will not weigh more than 1500 g (53 oz) at liftoff and will not contain more than 125 g (4.4 oz) of propellant or 320 N-sec (71.9 lb-sec) of total impulse. If my model rocket weighs more than 1 lb (453 g) at liftoff or has more than 4 oz (113 g) of propellant, I will check and comply with Federal Aviation Administration regulations before flying.
- **8. Flight Safety**. I will not launch my rocket at targets, into clouds, or near airplanes, and will not put any flammable or explosive payload in my rocket.
- **9.** Launch Site. I will launch my rocket outdoors, in an open area at least as large as shown in Table B.1, and in safe weather conditions with wind speeds no greater than 20 mph. I will ensure that there is no dry grass close to the launch pad, and that the launch site does not present risk of grass fires.
- 10. Recovery System. I will use a recovery system such as a streamer or parachute in my rocket so that is returns safely and undamaged and can be flown again, and I will use only flame-resistant or fireproof recovery system wadding in my rocket.
- 11. Recovery Safety. I will not attempt to recover my rocket from power lines, tall trees, or other dangerous places.

Table B.1 Launch Site Dimensions

Installed Total Impulse (N-sec)	Equivalent Motor Type	Minimum Site Dimensions (ft)
0.00-1.25	1/4 A, 1/2 A	50
1.26 - 2.50	A	100
2.51 - 5.00	В	200
5.01 - 10.00	\mathbf{C}	400
10.01-20.00	D	500
20.01-40.00	E	1000
40.01-80.00	F	1000
80.01-160.00	G	1000
160.01-320.00	Two Gs	1500

Source: National Association of Rocketry.

Annex C Glossary

This annex is not a part of the requirements of this NFPA document but is included for informational purposes only.

- **C.1** Aero Model. A miniature, unmanned flying device that includes the category of *model rocket* as defined in 3.3.7.2.
- **C.2** Skyrockets or Rockets with Sticks. Fireworks rockets not intended for re-use that meet the definition of *skyrocket* or *missile-type rocket* in the hazardous materials regulations of 49 CFR 172–173, "Department of Transportation Regulations." Fireworks rockets approved for transportation by the Department of Transportation (DOT) normally are classed as Fireworks UN 0335, Explosive 1.3G (formerly Class B Explosive, Special Fireworks), or Fireworks UN 0336, Explosive 1.4G (formerly Class C Explosive, Common Fireworks), depending on the quantity of pyrotechnic composition contained in the rocket. Skyrockets use a wooden stick for flight guidance and stability, while missile-type rockets use fins.

Annex D Sample Ordinance Adopting NFPA 1122

This annex is not a part of the requirements of this NFPA document but is included for informational purposes only.

D.1 The following sample ordinance is provided to assist a jurisdiction in the adoption of this code and is not part of this code.

ORDINANCE NO. _____

An ordinance of the [jurisdiction] adopting the [year] edition of NFPA [document number], [complete document title], and documents listed in Chapter 2 of that [code, standard]; prescribing regulations governing conditions hazardous to life and property from fire or explosion; providing for the issuance of permits and collection of fees; repealing Ordinance No. ______ of the [jurisdiction] and all other ordinances and parts of ordinances in conflict therewith; providing a penalty; providing a severability clause; and providing for publication; and providing an effective date.

BE IT ORDAINED BY THE [governing body] OF THE [jurisdiction]:

SECTION 1 That the [complete document title] and documents adopted by Chapter 2, three (3) copies of which are on file and are open to inspection by the public in the office of the [jurisdiction's keeper of records] of the [jurisdiction], are hereby adopted and incorporated into this ordinance as fully as if set out at length herein, and from the date on which this ordinance shall take effect, the provisions thereof shall be controlling within the limits of the [jurisdiction]. The same are hereby adopted as the [code, standard] of the [jurisdiction] for the purpose of prescribing regulations governing conditions hazardous to life and property from fire or explosion and providing for issuance of permits and collection of fees.

SECTION 2 Any person who shall violate any provision of this code or standard hereby adopted or fail to comply therewith; or who shall violate or fail to comply with any order made thereunder; or who shall build in violation of any detailed statement of specifications or plans submitted and approved thereunder; or fail to operate in accordance with any certificate or permit issued thereunder; and from which no appeal has been taken; or who shall fail to comply with such an order as affirmed or modified by a court of competent jurisdiction, within the time fixed herein, shall severally for each and every such violation and noncompliance, respectively, be guilty of a misdemeanor, punishable by a fine of not less than \$

ANNEX E 1122–11

nor more than \$____ or by imprisonment for not less than ____ days nor more than ____ days or by both such fine and imprisonment. The imposition of one penalty for any violation shall not excuse the violation or permit it to continue; and all such persons shall be required to correct or remedy such violations or defects within a reasonable time; and when not otherwise specified the application of the above penalty shall not be held to prevent the enforced removal of prohibited conditions. Each day that prohibited conditions are maintained shall constitute a separate offense.

SECTION 3 Additions, insertions, and changes — that the [year] edition of NFPA [document number], [complete document title] is amended and changed in the following respects:

List Amendments

SECTION 4 That ordinance No. ______ of [jurisdiction] entitled [fill in the title of the ordinance or ordinances in effect at the present time] and all other ordinances or parts of ordinances in conflict herewith are hereby repealed.

SECTION 5 That if any section, subsection, sentence, clause, or phrase of this ordinance is, for any reason, held to be invalid or unconstitutional, such decision shall not affect the validity or constitutionality of the remaining portions of this ordinance. The [governing body] hereby declares that it would have passed this ordinance, and each section, subsection, clause, or phrase hereof, irrespective of the fact that any one or more sections, subsections, sentences, clauses, and phrases be declared unconstitutional.

SECTION 6 That the *[jurisdiction's keeper of records]* is hereby ordered and directed to cause this ordinance to be published.

[NOTE: An additional provision may be required to direct the number of times the ordinance is to be published and to specify that it is to be in a newspaper in general circulation. Posting may also be required.] SECTION 7 That this ordinance and the rules, regulations, provisions, requirements, orders, and matters established and adopted hereby shall take effect and be in full force and effect [time period] from and after the date of its final passage and adoption.

Annex E Informational References

E.1 Referenced Publications. The documents or portions thereof listed in this annex are referenced within the informational sections of this code and are not part of the requirements of this document unless also listed in Chapter 2 for other reasons.

E.1.1 NFPA Publications. (Reserved)

E.1.2 Other Publications.

E.1.2.1 NAR Publications. National Association of Rocketry, P.O. Box 407, Marion, IA 52302.

Model Rocket Safety Code, 2001.

E.1.2.2 U.S. Government Publications. U.S. Government Printing Office, Washington, DC 20402.

Title 14, Code of Federal Regulations, Parts 101.1–101.25, "Federal Aviation Administration Regulations."

Title 49, Code of Federal Regulations, Parts 172–173, "Department of Transportation Regulations."

E.2 Informational References.

E.2.1 NAR Publications. National Association of Rocketry, P.O. Box 407, Marion, IA 52302.

Comprehensive CAR/NAR/TRA Rocket Motor Certification List.

E.2.2 TRA Publications. Tripoli Rocketry Association, Inc., P.O. Box 970010, Orem, UT 84097.

Comprehensive CAR/NAR/TRA Rocket Motor Certification List.

E.3 References for Extracts in Informational Sections. (Reserved)

Index

Copyright © 2007 National Fire Protection Association. All Rights Reserved.

The copyright in this index is separate and distinct from the copyright in the document that it indexes. The licensing provisions set forth for the document are not applicable to this index. This index may not be reproduced in whole or in part by any means without the express written permission of NFPA.

-A-	Module (definition)
Aero model (definition)	Motor reloading kit
Approved (definition)	Definition
Authority having jurisdiction (definition)	Prohibited activities
,, ,, ,, ,, ,, ,, ,,	Storage
-C-	Motorssee Model rocket motor; Rocket motor
Certified motor	
Definition	-N-
Code	National Association of Rocketry Model Rocket Safety Code Annex B
Adoption requirement	- · · · · · · · · · · · · · · · · · · ·
Definition	-0-
Sample ordinance adopting Annex D	Operation, of model rockets
Commercial manufacturer (definition)	operation, or model tockets
	-P-
-D-	Payloads, model rocket
Definitions	Power limits, model rocket
1 ,	Prohibited activities
-E-	Purpose of code
Eye safety	Turpose of code
	-R-
-F-	Recovery of rocket
Federal Aviation Administration requirements 4.4.2, A.4.2(1)	References
Flight paths, model rocket	Reloadable rocket motor
	Definition
-H-	Residential storage
High power rocket (definition)	Retrieval safety
High power rocket motor (definition)	Rocket
_	Definition
-I-	High power (definition)
Ignition system, model rocket	Model rocket (definition)
Installed total impulse	Skyrockets/rockets with sticks (definition)
Definition	Rocket engine
	Rocket motor
-L-	Definition
Labeled (definition)	Reloadable
Launch conditions	Definition
Launchers	Solid-propellant
Eye safety4.11	Definition
Launch safety	Rocket propellant (definition) 3.3.8; see also Solid-propellant
Launch site	rocket motor
Operating notice	
Size	-S-
Listed (definition)	Safety
-M-	Launch
	Model Rocket Safety Code Annex B
Materials, model rocket	Scope of code
Misfires	Shall (definition)
Model rocket (definition)	Should (definition) 3.2.7
Model rocket enginesee Model rocket motor	Skyrockets/rockets with sticks (definition)
Model rocket motor	Solid-propellant rocket motor
solid-propellant rocket motor	Definition
Certified	Spectators
Definition	Distances
Definition	Notification
Materials	Storage of motors
Prohibited activities	Structural parts
Requirements	Definition
Single-use	
Storage	-W-
For use by individuals under age 18 4.9.3, 5.1(10), 5.1(11)	· ·
Model Rocket Safety Code (Notional Association of Rocketty) Appey B	Weather for launching
(National Association of Rocketry) Annex B	Weight limits, model rocket