

Type F-2 Fiber Optic Media Interface Characteristics

1. SCOPE:

This slash sheet specifies the operational parameters and characteristics of a particular implementation of the SAE Linear, Token Passing Bus (LTPB) Interface Unit.

This slash sheet defines the following:

- a. The physical media interface: This slash sheet specifies the characteristics of the optical interface to the physical bus media.
- b. The minimum and maximum timing requirements for operation of this implementation of the LTPB.
- c. The data coding used to encode and decode the data for transmission.
- d. The default values to be loaded into the timers of the LTPB interface at power-up prior to intervention by the host processor.

2. REFERENCES:

There are no referenced publications specified herein.

PREPARED UNDER THE JURISDICTION OF
SAE COMMITTEE AS-2, INTERCONNECT NETWORKS

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright 2001 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in U.S.A.

TO PLACE A DOCUMENT ORDER: (724) 776-4970 FAX: (724) 776-0790 SAE WEB ADDRESS: <http://www.sae.org>

SAE AS4074/2

TYPE F-2 FIBER OPTIC MEDIA INTERFACE CHARACTERISTICS

Parameter	Description	Units	Requirement
COMMON CHARACTERISTICS			
-	Encoding Method and Symbol Set		Manchester II see Figure 1
R _d	Data Rate	Mbps	50 ± 0.01%
R _s	Signaling Rate	MBaud	100 ± 0.01%
T _o	Nominal Bit Time	ns	20
T _m	Minimum Duration Between Transitions	ns	10
T _{sr}	Maximum Station Response Time	ns	500
S _{itg}	System Minimum Intertransmission Gap	ns	280
W1	Optical Wavelength Lower	nm	800
W2	Optical Wavelength Upper	nm	880
BW	Spectral Bandwidth	nm	60
TPT	Token Passing Timer Initializ. Value	us	10.20
BAT	Bus Activity Timer Initializ. Value	us	15*(PSA+1)
RAT	Ring Admit. Timer Initializ. Value	ms	100
THT	Token Holding Timer Initializ. Value	us	50
TRT1	Token Rot. Timer 1 Initializ. Value	us	400
TRT2	Token Rot. Timer 2 Initializ. Value	us	300
TRT3	Token Rot. Timer 3 Initializ. Value	us	200
TRANSMITTER CHARACTERISTICS			
T _{po}	Transmitter Optical Power (Signal High)	dBm	-3.0 ± 1.5
T _{pr}	Transmitter Residual Power (Signal Low)	dBm	-16
T _{pl}	Transmitter Leakage Power (Tx Off)	dBm	-40
T _r	Transmitter Maximum Rise Time	ns	4
T _f	Transmitter Maximum Fall Time	ns	6
T _{pwd}	Transmitter Maximum Pulse Width Distortion	ns	2.4
T _{ous}	Transmitter Combined Over/Under-Shoot	%	5
T _{to}	Transmitter Nominal Bit Time	ns	20 ± 10%
T _{tm}	Transmitter Minimum Signaling Duration	ns	10 ± 5%
T _{ds}	Data Streaming Timer	ms	68 ± 1%
T _{sk}	Transmitter Redundant Media Skew Time	ns	150
P _t	Transmitter Preamble Length	Bit Times	16

SAE AS4074/2

TYPE F-2 FIBER OPTIC MEDIA INTERFACE CHARACTERISTICS (CONTINUED)

Parameter	Description	Units	Requirement
RECEIVER CHARACTERISTICS			
R _{po}	Receiver Maximum Optical Power Input	dBm	0
R _{or}	Receiver Operating Range	dB	21
R _{idr}	Receiver Intertransmission Dyn. Range	dB	15
R _{pm}	Receiver Minimum Optical Power Input	dBm	-32.5
R _{ous}	Receiver Combined Over/Under-Shoot	%	25
R _r	Receiver Maximum Rise Time	ns	5
R _f	Receiver Maximum Fall Time	ns	7
R _{pwt}	Receiver Maximum Pulse Width Distortion	ms	2.4
R _{to}	Receiver Nominal Bit Time	ns	20 ± 10%
R _{tm}	Receiver Maximum Signaling Rate	ns	10 ± 10%
R _{ber}	Receiver Maximum Bit Error Rate	-	10exp[-10]
P _r	Receiver Minimum Valid Preamble Length	Bit Times	12
MEDIA CHARACTERISTICS			
D _{core}	Fiber Core Diameter	um	200
D _{clad}	Fiber Cladding Diameter	um	240
NA	Fiber Minimum Numerical Aperture	-	0.2
D _{cm}	Maximum Total Dispersion	ns	3
A _{min}	Minimum Optical Attenuation	dB	11.5
A _{max}	Maximum Optical Attenuation	dB	28.5