

FEDERAL SUPPLY CLASS
4720REV.
A

AS4626

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.




FIGURE 1 - FLARELESS HOSE ASSEMBLY
STRAIGHT TO 90° ELBOW

THIRD ANGLE PROJECTION

CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: /2/ AS4623

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE, PARA ARAMID
REINFORCED, HEAVY-DUTY, 275 °F, 3000 psi FLARELESS,
TITANIUM FITTINGS, INCLUDING JUMP SIZE, STRAIGHT TO 90°

AS4626

SHEET 1 OF 6

REV.**A**

AS4626

REV.
A

TABLE 1 - HOSE AND FITTING DIMENSIONS

BASIC HOSE ASSEMBLY NO. AS4626 SIZE CODE	(SIZE)	/14/ FITTING TYPE	(THREAD T) (PER MIL-S-8879)	A1 MAX	A2 MAX	B GAGE BASIC	(C) HEX	D	E MAX	E MIN	F MAX	BALL SIZE MIN THRU /7/ MS19059 DASH NO.	BALL SIZE MIN THRU /7/ IN
E	.250	--	--	--	--	--	--	--	--	--	--	--	--
E	.250	S	.4375-20UNJF-3B	1.630	1.880	.2930	.56	.16	.770	.645	.69	4807	.109
E	.250	E	.5625-18UNJF-3B	1.695	1.960	.4120	.69	.16	.840	.715	.69	4807	.109
G	.375	R	.4375-20UNJF-3B	1.740	2.180	.2930	.56	.16	.770	.645	.80	4807	.109
G	.375	S	.5625-18UNJF-3B	1.835	2.180	.4120	.69	.16	.880	.715	.80	4812	.188
G	.375	E	.7500-16UNJF-3B	1.930	2.538	.5600	.88	.19	.970	.845	.80	4812	.188
H	.500	R	.5625-18UNJF-3B	2.145	2.538	.4120	.69	.16	.880	.715	.97	4812	.188
H	.500	S	.7500-16UNJF-3B	2.165	2.538	.5600	.88	.19	.970	.845	.97	4816	.313
H	.500	E	.8750-14UNJF-3B	2.675	2.780	.6730	1.00	.20	1.210	1.085	.97	4816	.313
J	.625	R	.7500-16UNJF-3B	2.860	3.375	.5600	.88	.19	.970	.845	1.15	4816	.313
J	.625	S	.8750-14UNJF-3B	2.905	3.375	.6730	1.00	.20	1.210	1.085	1.15	4818	.375
J	.625	E	1.0625-12UNJ-3B	2.920	3.665	.8100	1.25	.23	1.400	1.275	1.15	4818	.375
K	.750	R	.8750-14UNJF-3B	3.240	3.940	.6730	1.00	.20	1.210	1.085	1.38	4818	.375
K	.750	S	1.0625-12UNJ-3B	3.205	3.940	.8100	1.25	.23	1.400	1.275	1.38	4821	.469
K	.750	E	1.3125-12UNJ-3B	3.370	4.110	1.0620	1.50	.30	1.625	1.500	1.38	4821	.469
M	1.000	R	1.0625-12UNJ-3B	3.690	4.510	.8100	1.25	.23	1.400	1.275	1.66	4821	.469
M	1.000	S	1.3125-12UNJ-3B	3.740	4.510	1.0620	1.50	.30	1.625	1.500	1.66	4829	.719
M	1.000	E	1.5625-12UNJ-3B	3.570	4.740	1.3160	1.81	.04	1.825	1.700	1.66	4829	.719
N	1.250	--	--	--	--	--	--	--	--	--	--	--	--
N	1.250	S	1.5625-12UNJ-3B	4.330	5.310	1.3160	1.81	.04	1.825	1.700	2.32	4834	.875
N	1.250	--	--	--	--	--	--	--	--	--	--	--	--

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE, PARA ARAMID
REINFORCED, HEAVY-DUTY, 275 °F, 3000 psf FLARELESS,
TITANIUM FITTINGS, INCLUDING JUMP SIZE, STRAIGHT TO 90°

AS4626

SHEET 2 OF 6

REV.

A

AS4626

REV.
A

TABLE 2 - HOSE OR SLEEVE OUTSIDE DIAMETERS /10/

SLEEVE CODE	SLEEVE MATERIAL	TEMP. LIMIT °F	HOSE SIZE .250	HOSE SIZE .375	HOSE SIZE .500	HOSE SIZE .625	HOSE SIZE .750	HOSE SIZE 1.000	HOSE SIZE 1.250
-	(-) INDICATES HOSE ONLY NO SLEEVE (SEE AS4623)	275	--	--	--	--	--	--	--
A	FIRE SLEEVE (AS1072 SIL-FG) (5 min) /11/ /12/ /13/	275	.930/.730	1.070/.880	1.205/1.015	1.370/1.130	1.590/1.380	1.847/1.677	2.130/1.950
B	ABRASION SLEEVE SHRINK-ON (POLYOLEFIN AS1073-CODE B) /20/	275	.596/.524	.760/.680	.905/.825	1.030/.940	1.302/1.198	1.599/1.495	1.884/1.776

TABLE 3 - HOSE ASSEMBLY LENGTH TOLERANCES

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 18 in	±.125 in
18 THRU 36 in	±.250 in
OVER 36 THRU 50 in	±.500 in
OVER 50 in	±1%

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE, PARA ARAMID
REINFORCED, HEAVY-DUTY, 275 °F, 3000 ps1 FLARELESS,
TITANIUM FITTINGS, INCLUDING JUMP SIZE, STRAIGHT TO 90°

AS4626

SHEET 3 OF 6

REV.**A**

AS4626

REV.
A

TABLE 4 - WEIGHTS

HOSE OR SLEEVE CODE	HOSE PART OR SLEEVE	UNITS	HOSE SIZE .250	HOSE SIZE .375	HOSE SIZE .500	HOSE SIZE .625	HOSE SIZE .750	HOSE SIZE 1.000	HOSE SIZE 1.250
-	HOSE ONLY (SEE AS4623)	LB/IN	--	--	--	--	--	--	--
A	FIRE SLEEVE (AS1072 SIL-FG) (5 min) /15/	LB/IN	--	--	--	--	--	--	--
B	ABRASION SLEEVE (AS1073B) /20/	LB/IN	.0006	.0012	.0018	.0018	.0032	.0032	.0049
NONE	FIRE SLEEVE CLAMP	LB/EA	.020	.020	.021	.021	.025	.025	.032
NONE	FITTING END (STRAIGHT) /14/ /16/	R LB/EA	--	.077	.118	.186	.427	.823	--
NONE		S LB/EA	.054	.081	.135	.200	.476	.853	TBD /9/
NONE		E LB/EA	.074	.115	.193	.267	.591	1.000	--
NONE	FITTING END (90°) /14/ /16/	R LB/EA	--	.110	.143	.275	.460	.777	--
NONE		S LB/EA	.077	.121	.176	.297	.560	.947	TBD /9/
NONE		E LB/EA	.099	.154	.242	.410	.740	1.072	--

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE, PARA ARAMID
REINFORCED, HEAVY-DUTY, 275 °F, 3000 psi FLARELESS,
TITANIUM FITTINGS, INCLUDING JUMP SIZE, STRAIGHT TO 90°

AS4626

SHEET 4 OF 6

REV.**A**