


SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. A	FEDERAL SUPPLY CLASS 5340	
MA3294™	RATIONALE THIS TECHNICAL REPORT IS BEING STABILIZED BECAUSE IT COVERS TECHNOLOGY, PRODUCTS, OR PROCESSES WHICH ARE MATURE AND NOT LIKELY TO CHANGE IN THE FORESEEABLE FUTURE. STABILIZED NOTICE THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE G-3, AEROSPACE COUPLINGS, FITTINGS, HOSE, TUBING ASSEMBLIES COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.	
SAENORM.COM : Click to view the full PDF of ma3294a		
For more information on this standard, visit https://www.sae.org/standards/content/MA3294A/		THIRD ANGLE PROJECTION 
CUSTODIAN: G-3/G-3E		PROCUREMENT SPECIFICATION: NONE
	METRIC AEROSPACE STANDARD CLIP - SPRING, TENSION, OUTER 5.5 MM BOLT HOLE, AMS5525, METRIC	MA3294™ REV. A




FIGURE 1

TABLE 1

PART NUMBER	NOMINAL TUBE OD METRIC mm	SUITABLE FOR TUBE INCH	ØA	B	C	E	G	APPROX MASS kg/100
MA3294-02	3.2	0.125	8.1 - 8.7	13.1 - 13.6	8.1 - 8.7	0.7 - 0.9	35° - 45°	0.220
MA3294-02	4	---	8.1 - 8.7	13.1 - 13.6	8.1 - 8.7	0.7 - 0.9	35° - 45°	0.220
MA3294-04	5	0.188	10.0 - 10.6	14.0 - 14.5	10.0 - 10.6	0.7 - 0.9	35° - 45°	0.251
MA3294-04	6	0.250	10.0 - 10.6	14.0 - 14.5	10.0 - 10.6	0.7 - 0.9	35° - 45°	0.251
MA3294-06	8	0.312	11.9 - 12.5	15.0 - 15.5	11.9 - 12.5	0.7 - 0.9	35° - 45°	0.282
MA3294-07	10	0.375	13.7 - 14.3	15.9 - 16.4	13.7 - 14.3	0.7 - 0.9	35° - 45°	0.311
MA3294-08	---	0.438	15.7 - 16.7	17.3 - 17.8	15.9 - 16.5	0.9 - 1.1	45° - 55°	0.450
MA3294-08	12	0.500	15.7 - 16.7	17.3 - 17.8	15.9 - 16.5	0.9 - 1.1	45° - 55°	0.450
MA3294-10	14	0.562	17.5 - 18.5	17.7 - 18.7	17.7 - 18.3	0.9 - 1.1	45° - 55°	0.490
MA3294-11	16	0.625	19.3 - 20.3	18.6 - 19.6	19.5 - 20.1	0.9 - 1.1	55° - 65°	0.540
MA3294-12	18	0.688	21.1 - 22.1	20.0 - 20.5	21.3 - 21.9	0.9 - 1.1	55° - 65°	0.580
MA3294-13	20	0.750	23.0 - 24.0	21.0 - 21.5	23.2 - 23.8	0.9 - 1.1	55° - 65°	0.620
MA3294-14	22	0.875	24.6 - 25.6	22.0 - 22.5	24.8 - 25.4	0.9 - 1.1	55° - 65°	0.657
MA3294-15	25	1.000	27.3 - 28.3	23.5 - 24.0	27.5 - 28.1	0.9 - 1.1	55° - 65°	0.717
MA3294-16	30	1.125	32.3 - 33.3	25.8 - 26.3	32.5 - 33.1	0.9 - 1.1	55° - 65°	0.825
MA3294-17	32	1.250	34.3 - 35.3	27.0 - 27.5	34.5 - 35.1	0.9 - 1.1	55° - 65°	0.870
MA3294-18	40	1.500	42.3 - 43.3	30.8 - 31.3	42.5 - 43.1	0.9 - 1.1	55° - 65°	0.991